



## Sales specification

Property	Test method	Unit	Value
Epoxy Equivalent Weight	ASTM D 1652	g	240 - 256
Colour	ASTM D 5386	Pt /Co scale	50 max
Density at 25°C	ASTM D4052	kg/l	0.945-0.965
Water content	ASTM D 4928	% (m/m)	0.1 max
Appearance	visual	-	Clear liquid, free from suspended matter

## Test methods

ASTM Standards are published by the American Society for Testing and Materials, 100 Barr Harbor Drive, west Conshohocken, PA 19428-2959, USA or can be found under [www.astm.org](http://www.astm.org).

ISO standards are published under the supervision of the International Standards Organisation and are available from National Standards Institutes.

SMS methods mentioned are available from Hexion Specialty Chemicals B.V.

## Transportation and storage

Information on transport, storage, suitable materials for tank construction, etc, is available from Hexion Specialty Chemicals, via local representative or distributor.

## Handling precautions

For more detailed information on all aspects relating to Health, Safety and Handling, reference should be made to the Safety Data Sheet of CARDURA N-10, which is available from your local Hexion Specialty Chemicals representative or distributor. The precautions advised therein should be strictly observed

CARDURA and VERSATIC are trade marks of HEXION SPECIALTY CHEMICALS

*The information contained in this publication is to the best of our knowledge, true and accurate, but any recommendations or suggestions which may be made are without guarantee, since the conditions of use are beyond our control. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.*